



Codo 45° , Roscado / SW



ROSCADO (THREADED)									
NW	2000Lb			3000Lb			6000Lb		
	Bø	C	Peso~	Bø	C	Peso~	Bø	C	Peso~
Pulg.	mm.	mm.	Kg%	mm.	mm.	Kg%	mm.	mm.	Kg%
1/4	25,5	19	11,5	25,5	19	11,5	38	25,5	40,5
3/8	25,5	19	10,5	38	25,5	36,5	38	25,5	38,5
1/2	38	25,5	30	38	25,5	34	46	28,5	61
3/4	38	25,5	26,8	46	28,5	53,5	55,5	33,5	102
1	46	28,5	40,8	55,5	33,5	92	62	35	117,5
1 1/4	55,5	33,5	63,5	62	35	96,5	75,5	43	207
1 1/2	62	35	74,8	75,5	43	183,5	84	43,5	261
2	75,5	43	119,3	84	43,5	193	101,5	52,5	437
2 1/2	101,5	52,5	346	101,5	52,5	346	120,5	63,5	700
3	118	63,5	545	120,5	63,5	545	152,5	79,5	1.416
4	146	79,5	950	152,5	79,5	950	---	---	---

Codo 45°, Roscado / SW



S. W. - ENCHUFE Y SOLDADURA										
NW	3000Lb					6000Lb				
	B∅ mm.	C mm.	D∅ mm.	G mm.	Peso Kg%	B∅ mm.	C mm.	D∅ mm.	G mm.	Peso Kg%
1/4	25,5	19	14	9,5	9,5	---	---	---	---	---
3/8	25,5	19	17,5	11	9	---	---	---	---	---
1/2	38	25,5	21,7	11	26	38	25,5	21,7	12,5	31
3/4	38	25,5	27,1	12,5	25	46	28,5	27,1	14,5	52
1	46	28,5	33,8	14,5	38,1	55,5	33,5	33,8	16	92
1 1/4	55,5	33,5	42,6	16	60,8	62	35	42,6	14,5	102
1 1/2	62	35	48,7	16	70,8	75,5	43	48,7	17,5	191,5
2	75,5	43	61,1	17,5	113,5	84	43,5	61,1	15	228,5
2 1/2	101,5	52,5	73,8	24	336	101,5	52,5	73,8	20,5	404
3	118	63,5	89,8	32	470	118	63,5	89,8	28,5	580
4	146	79,5	115,4	38	900	146	79,5	115,4	38	1.065



MATERIALES INDUSTRIALES DE COATZACOALCOS

servicio.clientes@micsacv.com

(921)211-3300